

HEATING SYSTEMS 2013

ACCESSORIES FOR AN AMAZING INSTALLATION

DIMMER
PRESENCE DETECTOR
REMOTE CONTROL
RECEIVER ON/OFF

NEW IDEAS FOR PROFESSIONAL USE



9001 KIT DIMMER 2000W AND REMOTE CONTROL

230V wireless wall fixing receiver with dimmer function for resistive/infrared heaters up to 2000W. Dimming on 3 pre-set levels selectable with the wireless transmitter. If controlled with a 4-channel transmitter the first 3 channels activate the levels. The 4th channel do the switching off. Input for manual control. IP54 protection.

Wireless. Remote control with wireless transmitters and with wall fixing support.

Selectable power 100%, 66%, 50%, OFF

Easy installation. Suitable for false ceiling.

Input. Push-button input for manual commands.

Characteristics:

- Dimmer function on 3 levels
- Power supply 230V
- Heater control up to 2000W

DIMMER TECHNICAL SPECIFICATIONS

Power supply 230V

Minimum settable load 25W

Maximum settable load 2000W

Operating temperature range -20°C +50°C

Protection level IP54

Dimensions 165 x 64 x 30 mm

REMOTE CONTROL TECHNICAL SPECIFICATIONS

Power supply 3V ± 10% (lithium battery CR2032)

Operating temperature -10°C +55°C



9003 KIT PRESENCE DETECTOR AND RECEIVER

2-channel presence detector via radio with battery for external use. ON/OFF function. IP44 protection. Mod 9003 senses the presence of human body by its warm and not only movement.

Possible settable functions:

- Light intensity: for switch on and off depending by environment brightness
- Activation distance: adjustable detection range
- Adjustable ON/OFF time

RECEIVER TECHNICAL SPECIFICATIONS

Power supply 230Vac

Maximum resistive load 2000W (x 2 outlets)

Operating temperature range -20°C +50°C

Protection IP54

Dimensions 205 x 145 x 85 mm

PRESENCE DETECTOR TECHNICAL SPECIFICATIONS

Power supply 6Vdc (UM-3 AA battery 1.5V x 4)

Signal range approx 100m (free space)

Detecting range 12m/180°



ON/OFF time adjustable from 5 sec. to 5 min.
 LUX adjustable from 5 LUX to ∞
 Protection IP44
 Dimensions 87 x 125 x 120 mm

9004 KIT RECEIVER AND REMOTE CONTROL

Kit 9004 permits you to switch On and Off up to two MO-EL heaters separately.

RECEIVER TECHNICAL SPECIFICATIONS

Power supply 230Vac
 Maximum resistive load 2000W (x 2 outlets)
 Operating temperature range -20°C +50°C
 Protection IP54
 Dimensions 205 x 145 x 85 mm

REMOTE CONTROL TECHNICAL SPECIFICATIONS

Power supply 3V ± 10% (lithium battery CR2032)
 Operating temperature -10°C +55°C



724 DIMMER 4 CHANNELS

Zone dimmer for controlling remotely the power of infrared heaters.
 Up to four MO-EL heaters with power dimming and separated ON/OFF
 Easy to connect.
 CE GS certified.
 Dimensions: 28 cm high, 22 cm wide, 12 cm deep.
 Each Channel can operate up to 2000W
 Power Supply 400V 50Hz



ACCESSORIES	9001	9002	9003	9004	724
Description	Kit dimmer and remote control	Remote control (Spare parts)	Presence detector and receiver	Receiver ON/OFF and remote control	Dimmer 4 channels
Master Box	1pc	1pc	1pc	1pc	1pc
Made in	ITALY	ITALY	ITALY	ITALY	P.R.C.
Fitting	all items	all items	all items	all items	all items
IP Rate	IP65	IP65	IP65	IP65	
Price in Euro	230,90	48,60	324,10	230,90	384,00

NEW





ITALY

MO-EL S.R.L. VIA L. GALVANI N°18, POSTAL CODE 42027,
MONTECCHIO EMILIA, RE. ITALIA
PH. 0039 0522 868011 - FAX 0039 0522 864223
E-MAIL: INFO@MO-EL.COM - WEB: WWW.MO-EL.COM



The manufacturer reserves the right to modify products' features without prior notice.
Technical data written in this leaflet are based on indicative parameters.